

True leaders do not follow
...they lead the way

WHAT ARE THE ROAD WARNING SIGNS?

- Road warning signs are panels with symbols and legends that give advance notice of the presence and nature of a hazard or unexpected event on the road.
- These signs aim to alert users so they can take the necessary precautions, protecting themselves and other road users.
- These are square panels with rounded corners, mounted diagonally, except for **SP-33 School**.
- Preventive signs are classified into seven functional groups:

Group 1: These signs are intended to warn drivers of upcoming changes in the geometric characteristics of the road, such as curves or steep slopes.

Group 2: These signs are meant to alert drivers of the proximity of an intersection, such as a crossing, road split, or junction.

Group 3: These signs are designed to give advance notice to drivers of upcoming changes in the road surface, such as speed bumps or pavement variations.

Group 4: These signs warn drivers of approaching temporary or physical restrictions on the road, such as narrowings or clearance limitations.

Group 5: These signs alert drivers of road modifications, such as changes in traffic direction, the presence of devices requiring speed reduction or a complete stop, and crossings with other users or vehicles.

Group 6: These signs notify drivers of special conditions on the road caused by environmental or situational changes.


Group 7: These signs provide additional information that complements other regulatory signs.



Group 1



Group 2



Group 3

Features

- Material: Made from 16-gauge galvanized sheet.
- Background: Traffic yellow reflective, except for **SP-33 School**, which must have fluorescent lime green reflective background.
- Symbols, lettering, and borders: Black opaque vinyl, except for symbols on **SP-31a** and **SP-31b (STOP or YIELD)** and **SP-19b** (Exit with deceleration speed).
- Additional panels: Traffic yellow reflective background with symbols, lettering, and borders in black opaque vinyl, except for **SP-B Schedule**, which should have a fluorescent lime green reflective background when placed alongside **SP-33 School**.



Group 4

Dimensions and other measurements are nominal and may vary by $\pm 2\%$



Group 5



Group 6

Dimensions

SPEED	REGULATORY SIGN DIMENSIONS*	LINES OF LEGENDS OR PICTOGRAMS**	SUPPLEMENTARY PANEL FOR THE SIGN (ft)
	0.98 x 0.98	1	1.38 x 0.32
		2	1.38 x 0.49
		3	1.38 x 0.65
≤ 19	1.47 x 1.47	1	2 x 0.49
		2	2 x 0.74
		3	2 x 0.98
≤ 25	2 x 2	1	2.8 x 0.65
		2	2.8 x 0.98
		3	2.8 x 1.31
≤ 37	2.32 x 2.32	1	3.28 x 0.82
		2	3.28 x 1.23
		3	3.28 x 1.64
≤ 50	2.82 x 2.82	1	4 x 0.98
		2	4 x 1.47
		3	4 x 1.96
≤ 50	3.83 x 3.83	1	4.98 x 1.31
		2	4.98 x 1.96
		3	4.98 x 2.62



Group 7

Height

For both urban and interurban roads, the lower edge of the sign panel should be installed at 8.2 ft above the sidewalk or road shoulder.