

True leaders do not follow
...they lead the way



Group 1



Group 2

Features

- Material: Made from 16-gauge galvanized sheet.
- Reflective background: White in general, except for **SR-6 STOP**, which must have a red reflective background.
- Perimeter ring and diagonal stripe: Red reflective, except for **SR-7b Right-of-Way** and **SR-7c Priority of Use**, where the perimeter stripe must be green reflective.
- Symbols, characters, and borders: Black opaque vinyl, except for **SR-6 STOP**.
- Additional panels: White reflective background with symbols, characters, and borders in black opaque vinyl, except for **SR-A ONE AND ONE**, which has a red reflective background with symbols and borders in white reflective material.

WHAT ARE THE REGULATORY TRAFFIC SIGNS?

- These are post-mounted panels designed to alert road users—whether in rural or urban environments—about physical limitations or legal prohibitions that regulate vehicle circulation.
- The signs are generally circular, except for **SR-6 STOP**, **SR-7a YIELD**, **SR-7b RIGHT-OF-WAY**, and **SR-7c PRIORITY OF USE** signs.
- When additional details are required, a rectangular auxiliary panel with rounded corners is added below the main sign. This secondary sign panel displays a legend indicating the specific restriction, tailored to the local conditions.
- Regulatory signs are divided into seven functional groups:
 - Group 1:** These signs are intended to regulate right-of-way at intersections without traffic lights.
 - Group 2:** These signs are meant to limit vehicle movement due to temporary conditions or roadway constraints.
 - Group 3:** These signs are designed to define permitted or mandatory maneuvers for certain users.
 - Group 4:** These signs serve to designate exclusive use of a road or lane for a specific group of users.
 - Group 5:** These signs aim to prohibit a movement or action for a specific group of users.
 - Group 6:** These signs restrict access to certain users or vehicle types. When applicable to pedestrians or multiple vehicles, their pictograms may be combined on a single panel.
 - Group 7:** These signs provide additional information that complements other regulatory signs.



Group 3

Dimensions and other measurements are nominal and may vary by $\pm 2\%$



Group 4



Group 5



Group 6

Supplementary sign panel



Group 7

Dimensions

VELOCIDAD	DIAMETER - REGULATORY SIGN*	LINES OF LEGENDS OR PICTOGRAMS**	SUPPLEMENTARY PANEL FOR THE SIGN (ft)
≤ 19	0.98	1	0.98 x 0.33
		2	0.98 x 0.49
		3	0.98 x 0.65
≤ 25	1.47	1	1.47 x 0.49
		2	1.47 x 0.73
		3	1.47 x 0.98
≤ 38	1.96	1	1.96 x 0.65
		2	1.96 x 0.98
		3	1.96 x 1.31
≤ 56	2.46	1	2.46 x 0.82
		2	2.46 x 1.23
		3	2.46 x 1.64
≤ 56	2.9	1	2.95 x 0.98
		2	2.95 x 1.47
		3	2.95 x 1.96
≤ 56	3.93	1	3.93 x 1.31
		2	3.93 x 1.96
		3	3.93 x 2.62

Height

For both urban and interurban roads, the lower edge of the sign panel should be installed at 8.2 ft above the sidewalk or road shoulder.